

# Data sheet for household cooker hoods

In acc. with delegated regulation (EU) No. 65/2014 and regulation (EU) No. 66/2014

Miele		
Model identifier	DA 1260	
Annual Energy Consumption ( $AEC_{hood}$ )	kWh/year	91.6
Energy efficiency class		C
Energy efficiency index ( $EEI_{hood}$ )		82.1
Fluid Dynamic Efficiency ( $FDE_{hood}$ )		16.3
Fluid Dynamic Efficiency class		
A (most efficient) to G (least efficient)		D
Lighting Efficiency ( $LE_{hood}$ )	lx/W	55.0
Lighting Efficiency class		
A (most efficient) to G (least efficient)		A
Grease Filtering Efficiency	%	95.1
Grease Filtering Efficiency class		
A (most efficient) to G (least efficient)		A
Airflow at best efficiency point	m³/h	317.1
Air flow (min. speed)	m³/h	275
Air flow (max. speed)	m³/h	355
Air flow (intensive or boost setting)	m³/h	545
Max. air flow ( $Q_{max}$ )	m³/h	545.0
Air pressure at best efficiency point	Pa	313
Airborne acoustical A-weighted sound power emissions (min. speed)	dB	57
Airborne acoustical A-weighted sound power emissions (max. speed)	dB	64
Airborne acoustical A-weighted sound power emissions (intensive or boost setting)	dB	74
Electrical power input at best efficiency point	W	169.0
Nominal power of lighting system	W	6.0
Average illumination of the lighting system on the cooking surface	lx	330
Time increase factor		1.4